

NOTES:

Current Rating: 8A
Voltage Rating: 300V
Contact Resistance: 8miliohm Max
Withstand Voltage: AC 1500V
Insulation Resistance: 1000Megohm Min
Operation Temperature: -40℃ to +105℃

Housing Material: PA66+30%GF(UL94V-0) $\Delta 3$
Contact Material: Brass
Inlay Material: Brass


Ordering Information:

P M 350 - 1 S XX A SM 2 N


M=Male
Pitch
350=3.50
No. of Pins
02-20P
Color
A=Green
Contact Plated
SM=Matte Tin
Blank=W/T WCON
N=W/O WCON
Series No.

ITEM	Pitch	Mating
Standard	3.50	PF350
Alternate		

11P	48.80 ±0.30	35.00 ±0.30			
10P	45.30 ±0.30	31.50 ±0.30	20P	80.30 ±0.40	66.50 ±0.40
9P	41.80 ±0.30	28.00 ±0.30	19P	76.80 ±0.40	63.00 ±0.40
8P	38.30 ±0.20	24.50 ±0.20	18P	73.30 ±0.40	59.50 ±0.40
7P	34.80 ±0.20	21.00 ±0.20	17P	69.80 ±0.40	56.00 ±0.40
6P	31.30 ±0.20	17.50 ±0.20	16P	66.30 ±0.40	52.50 ±0.40
5P	27.80 ±0.20	14.00 ±0.20	15P	62.80 ±0.40	49.00 ±0.40
4P	24.30 ±0.20	10.50 ±0.20	14P	59.30 ±0.30	45.50 ±0.30
3P	20.80 ±0.20	7.00 ±0.20	13P	55.80 ±0.30	42.00 ±0.30
2P	17.30 ±0.20	3.50 ±0.10	12P	52.30 ±0.30	38.50 ±0.30
PIN	A	B	PIN	A	B







$\Delta 5$
W/O WCON



W/T WCON

Recommended P.C.B Layout (Top Side)
(PCB BOARD TOLERANCE±0.05)



A5	2020/11/14	Add UL Logo & DIM; Add W/O WCON SPEC&P/N $\Delta 5$	XSR	OPERATION	DRAW	DATE	SCALE	FIT	PART NO.
A4	2018/03/12	Modify $\Delta 4$		X.X ±0.40	XSR	2020/11/14	UNIT	mm	PM350-1SXXASM2(N) $\Delta 4 \Delta 5$
A3	2013/06/05	Modify The Housing Material $\Delta 3$		X.XX ±0.25	CHECK	DATE	SIZE	A4	TITLE:
A0	2011/06/07	NEW		X.XXX ±0.15	APPROVE	DATE	SHEET	1/1	3.50mm Pitch Male
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	Angle ± 3°			PROJ.		Pluggable Terminal Blocks
				DIM TOL					Customer NO.

WCON
Http: www.wcon.com

WCON-Dongguan
Tel: +86 769 85358920
Fax: +86 769 85358915
E-mail: sales@wcon.com

WCON-Kunshan
Tel: +86 512 57468408
Fax: +86 512 57468468
E-mail: salesks@wcon.com