

HSF


NOTES:
 Current Rating:10A
 Voltage Rating:300V
 Contact Resistance:20milliohm Max
 Withstand Voltage:AC2000V
 Insulation Resistance:1000Megohm Min
 Screw Torque: 4.4 lbf.in
 Wire range: 12-30AWG
 Operation Temperature: -40℃ to +105℃

Housing Material:PA66 UL94V-0
 Cover Material:PA66 UL94-V0
 Screw: Steel
 Pin Block: Brass
 Contact: Phosphor Bronze

Ordering Information:

P F 500 - B XX A SM W 1
 F=Female Pitch 500=5.00 No. of Pins 02-24P Color A=Green Contact Plated SM=Matte Tin Type W=With Screw


13P	75.08 ±0.40	60.00 ±0.35			
12P	70.08 ±0.40	55.00 ±0.35	24P	130.08 ±0.40	115.00 ±0.40
11P	65.08 ±0.40	50.00 ±0.35	23P	125.08 ±0.40	110.00 ±0.40
10P	60.08 ±0.35	45.00 ±0.30	22P	120.08 ±0.40	105.00 ±0.40
9P	55.08 ±0.35	40.00 ±0.30	21P	115.08 ±0.40	100.00 ±0.40
8P	50.08 ±0.35	35.00 ±0.30	20P	110.08 ±0.40	95.00 ±0.35
7P	45.08 ±0.35	30.00 ±0.30	19P	105.08 ±0.40	90.00 ±0.35
6P	40.08 ±0.35	25.00 ±0.30	18P	100.08 ±0.40	85.00 ±0.35
5P	35.08 ±0.35	20.00 ±0.30	17P	95.08 ±0.40	80.00 ±0.35
4P	30.08 ±0.35	15.00 ±0.30	16P	90.08 ±0.40	75.00 ±0.35
3P	25.08 ±0.35	10.00 ±0.30	15P	85.08 ±0.40	70.00 ±0.35
2P	20.08 ±0.35	5.00 ±0.30	14P	80.08 ±0.40	65.00 ±0.35
位数	A	B	位数	A	B



				OPERATION		DRAW	DATE	SCALE	FIT	PART NO.		
				X.X	±0.40							
A1	2019/05/19	Add Explosion view & Material List	—	X.XX	±0.25	CHECK	DATE	UNIT	mm	PF500-BXXASMW1	Http: www.wcon.com	
A0	2019/03/19	NEW	—	X.XXX	±0.15	APPROVE	DATE	SIZE	A4			
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	Angle	± 3°			SHEET	1/2	Customer NO.	WCON-Dongguan Tel: +86 769 85358920 Fax: +86 769 85358915 E-mail: sales@wcon.com	
				DIM	TOL			PROJ.	⌀			

WCON-Kunshan
 Tel: +86 512 57468408
 Fax: +86 512 57468468
 E-mail: salesks@wcon.com

HSF



(6)	Screw 2	MA025-1SNI02	N	C1018
(5)	Contact	TPT051-PSM001	N	C5191R-H T=0.4mm
(4)	Pin Block	BL025-1SNI01	N	C3604
(3)	Screw 1	MA025-1SXX01	N	C1018
(2)	Cover	XPf500-XXB1XN4	1	PA66 UL94-V0
(1)	Housing	XPf500-XXB1XW2	1	PA66 UL94-V0
ITEM	TITLE	PART NO.	Q'TY	Material

A1

				OPERATION		DRAW XSR	DATE	SCALE	FIT	PART NO. PF500-BXXASMW1	WCON Http: www.wcon.com	
				X.X	±0.40		2019/05/19	UNIT	mm inch			
A1	2019/05/19	Add Explosion view & Material List	——	X.XX	±0.25	CHECK	DATE	SIZE	A4	TITLE: 5.00mm Pitch Female Pluggable Terminal Blocks	WCON—Dongguan	
A0	2019/03/19	NEW	——	X.XXX	±0.15						Tel: +86 769 85358920	
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	Angle	± 3°	APPROVE	DATE	SHEET	2/2	Customer NO.	Tel: +86 512 57468408	
				DIM	TOL						Fax: +86 769 85358915	
											E-mail: sales@wcon.com	
										E-mail: salesks@wcon.com		

WCON-Kunshan
Tel: +86 512 57468408
Fax: +86 512 57468468
E-mail: sales@wcon.com